

Specification

Title of the Invention

Broadcasting Control System and Method in ATM Ring Network

5

Background of the Invention

The present invention relates to a
broadcasting control system and broadcasting control
method in an ATM (Asynchronous Transfer Mode) ring
10 network.

Conventionally, in an ATM ring network system,
a plurality of nodes (#1 to #n) 2-1 to 2-n are connected
into a ring shape, as shown in Fig. 4. In this
arrangement, when a control user cell (to be referred to
15 as a cell hereinafter) B is sent from the node 2-1, each
of the nodes 2-2 to 2-n generates one response cell C in
response to the cell B, so the number of response cells
C increases toward the downstream.

Each of the above-described response cells C
20 has a No (identification data) C1 of itself, e.g., a
node No or VPI (Virtual Path Identifier) value in the
payload, as shown in Fig. 6. The node 2-1 as a parent
control node confirms the response states of the nodes
2-2 to 2-n on the basis of response data C2 in the
25 payload.

Fig. 5 shows each of the nodes 2-1 to 2-n.
Referring to Fig. 5, each of the nodes 2-2 to 2-n

comprises an ATM switch (ATM SW) 21, a user cell
receiving section 22 for receiving a cell branched from
the ATM switch 21, a user cell transmitting section 23
for transmitting a cell through the ATM switch 21, and
5 an MPU (Micro Processing Unit) 24 for transmitting
response data to the user cell transmitting section 23
on the basis of control data output from the user cell
receiving section 22. Reference numeral 201 denotes an
upstream transmission line; and 202, a downstream
10 transmission line.

When an ATM cell containing control data is
broadcast from the node 2-1 for control, the ATM switch
21 in each of the nodes 2-2 to 2-n branches a cell. In
addition, in each of the nodes 2-2 to 2-n, an ATM cell
15 containing response data generated by the user cell
transmitting section 23 is sent to the node 2-1 through
the ATM switch 21.

In the above-described conventional ATM ring
network system, since n-1 response cells C as shown in
20 Fig. 6 are almost simultaneously generated for one
broadcasting from a node, the user cell receiving
section of each node is required to have high processing
performance. For this reason, the ATM ring network
system itself becomes uneconomical.

25 For example, the ITU recommendations I.630 are
defined for ATM switching as recommendations for a 1 : 1
system. However, a 1 : n system is a subject for future

examination and has not been standardized yet.

Summary of the Invention

It is an object of the present invention to provide a broadcasting control system and method in an ATM ring network, which can build an economical system.

In order to achieve the above object, according to the present invention, there is provided a broadcasting control system in an ATM ring network in which a control cell containing control information is transmitted by ATM (Asynchronous Transfer Mode) between a plurality of nodes connected into a ring shape, each of the nodes comprising receiving means for receiving a control cell from an upstream node, and transmitting means for writing response information of the self node for the control information contained in the received control cell in an area corresponding to the self node in the control cell and transmitting the control cell to a downstream node.

Brief Description of the Drawings

Fig. 1 is a block diagram showing an ATM ring network system according to an embodiment of the present invention;

Fig. 2 is a block diagram showing each of nodes shown in Fig. 1;

Fig. 3 is a view showing the structure of a control user cell shown in Fig. 1;

Fig. 4 is a block diagram showing a

conventional ATM ring network system;

Fig. 5 is a block diagram showing each of nodes shown in Fig. 4; and

Fig. 6 is a view showing the structure of a response cell shown in Fig. 4.

Description of the Preferred Embodiment

The present invention will be described below in detail with reference to the accompanying drawings.

Fig. 1 shows an ATM ring network system according to an embodiment of the present invention. Referring to Fig. 1, the ATM ring network system of this embodiment has a plurality of nodes (#1 to #n) 1-1 to 1-n connected into a ring shape. For the descriptive convenience, the nodes 1-1 to 1-n are assigned VPI values 1 to n, respectively. Upstream and downstream transmission lines 101 and 102 are connected to the nodes 1-1 to 1-n.

A control user cell (to be referred to as a cell hereinafter) A1 sent from the node 1-1 is input to the node 1-2 through the downstream transmission line 102. The node 1-2 rewrites a data portion related to itself in the received cell A1 to response data and sends a rewritten cell A2 to the downstream node 1-3.

Upon receiving the cell A2, the node 1-3 rewrites the response data and sends the rewritten cell A3 to the downstream. Subsequently, the nodes 1-4 to 1-n repeat the same operation as described above, and

00902T 082E 260
finally, a cell A_n is sent from the node 1-n to the node
1-1. Thus, all data in the cell A₁ are rewritten to
response data (cells A₂ to A_n) by the nodes 1-2 to 1-n
and finally terminated at the node 1-1 and the response
5 data are detected.

Fig. 2 shows each of nodes 1-1 to 1-n shown in
Fig. 1. Referring to Fig. 2, each of the nodes 1-1 to
1-n comprises an ATM switch (ATM SW) 11 for terminating
a cell input from the upstream transmission line 101, a
10 user cell receiving section 12 for receiving and
transferring the cell terminated by the ATM switch 11, a
user cell transmitting section 13 for outputting a
response cell to the downstream transmission line 102
through the ATM switch 11 in response to the cell
15 transferred from the user cell receiving section 12, and
an line control MPU 14 for receiving control data output
from the user cell receiving section 12 and outputting
response data to the user cell transmitting section 13.

Fig. 3 shows the structure of the
20 above-described cells A₁ to A_n. Referring to Fig. 3,
the cells A₁ to A_n comprise a broadcasting control data
portion 21, a plurality of flags (F) 22 representing the
end of reception in units of nodes, and a plurality of
response message portions 23 corresponding to the nodes.
25 The cells A₁ to A_n contain the flags 22 and response
message portions 23 in number equal to the number n-1 of
control target nodes.

The operation of the above-described ATM ring network system will be described next. For the 1-bit flag 22, "0" represents control, and "1" represents response.

5 For control by broadcasting, control data is generated by the user cell receiving section 12 of the node 1-1 and output to the user cell transmitting section 13 through the MPU 14. The user cell transmitting section 13 writes the control data from the
10 MPU 14 to the broadcasting control data portion 21 to assemble the cell A1, and outputs the assembled cell A1 to the downstream transmission line 102 through the ATM switch 11. Thus, the cell A1 is transferred to the node 1-2 through the downstream transmission line 102. At
15 this time, all the flags 22 have logic "0".

 The cell A1 received by the node 1-2 is received by the user cell receiving section 12 through the ATM switch 11. The user cell receiving section 12 of the node 1-2 outputs the control data written in the
20 broadcasting control data portion 21 of the received cell A to the MPU 14 and directly transfers the received cell A1 to the user cell transmitting section 13.

 In the node 1-2, the MPU 14 executes control in the device in accordance with the received control
25 data and outputs the control result to the user cell transmitting section 13 as response data. The user cell transmitting section 13 rewrites the flag 22

corresponding to its own VPI value to "1" and rewrites
the response message portion 23 to the response data
received from the MPU 14, thereby generating the cell A2.
After that, the cell A2 is transferred to the node 1-3
5 as a downstream device through the ATM switch 11.

The above processing operation is sequentially
repeatedly executed by the nodes 1-3 to 1-n until the
node 1-1 receives the cell An from the node 1-n.

In the node 1-1, the cell An from the node 1-n
10 through the upstream transmission line 101 is received
by the user cell receiving section 12 through the ATM
switch 11, and the contents of the flags 22 and response
message portions 23 corresponding to the nodes 1-2 to
1-n, respectively, in the cell An are confirmed.

15 According to this embodiment, only one kind of
control user cell A need be detected and generated
independently of the number of control target nodes.
Hence, the number of nodes of a constructable network is
irrelevant to the performance of the ATM cell
20 disassemble/generation function, and an economical
system can be built. That is, as compared to the
conventional case wherein response cells are
individually generated and transferred to the control
source by the nodes, the dependence on the performance
25 of the ATM cell disassemble/generation function is small
and an economical control function can be realized.
Note that the present invention can also be applied as

an alarm polling scheme.

As has been described above, according to the present invention, in an ATM ring network system in which an ATM user cell is transmitted between a plurality of nodes connected into a ring shape in an asynchronous transfer mode, when each of the plurality of nodes is to operate the remaining nodes in accordance with control information, a control cell containing the control information is transmitted to the remaining nodes by broadcasting, and upon receiving the control cell containing the control information from another node, a portion of the control cell, which corresponds to the self station, is rewritten to the response contents of the self station, and the cell is transmitted to the downstream, thereby building an economical system.